Maintenance instructions - vinyl

THE MAINTENANCE KIT CONSISTS OF:

1 liter Bona Tile & Laminate Cleaner

1 liter Bona Tile & Laminate Polish: 50m²/liter

1. TAKE SOME PRECAUTIONS

- 1. Exposure to direct sunlight can cause colour changes.
- 2. Carpets and furniture should be moved from time to time to avoid permanent colour changes.
- 3. Apply appropriate protection to the legs of the furniture.
- 4. Apply freely rotating, non-rubber wheels to chairs with castors and/or use protective matting.
- 5. Please bear in mind that pets with sharp nails can leave deep scratches on the floor
- 6. Place beige, felt floor protectors under chair and table legs; do not used coloured floor protectors!
- 7. Prolonged contact with rubber can cause permanent stains. Do not use rubbed-backed doormats.
- 8. Avoid contact with dirt, sand, grit and substances such as oil or asphalt by placing carpets and vinyl-back doormats at the front- and backdoor.
- 9. NEVER use aggressive cleaning products, soap or abrasive cleaners or cleaning products that contain oil or wax.

2. FIRST TREATMENT AFTER INSTALLATION

Clean the floor with a vacuum cleaner with soft parquet brush. Only 5 days after installation a maintenance product can be used. Use Bona Tile & Laminate Polish.

- 1. Remove dirt/sand and clean the floor with Bona Tile & Laminate cleaner. You can find the instructions under the item 'Regular cleaning': Make sure the floor is completely dry before you use the polish.
- 2. Shake the can Bona Tile & Laminate Polish before use. Pour the polish on the floor in a wavy line of 3-4 cm wide. Work on a surface of 3m² at a time. Attention: do not use fibre, cotton or sponge cloths, etc.
- 3. Spread the polish on the surface (3m²) with a woollen cleaning cloth. Make sure that the cloth stays moist with polish.
- 4. Leave the floor to dry for at least 1h before walking on it. Attention: Reduce draft and dust to a minimum while the floor isn't dry.















Maintenance instructions - vinyl

THE MAINTENANCE KIT CONSISTS OF:

1 liter Bona Tile & Laminate Cleaner

1 liter Bona Tile & Laminate Polish: 50m²/liter

3. REGULAR CLEANING

For weekly Maintenance use Bona Tile & Laminate Cleaner.

- 1. Vacuum clean or sweep the floor to remove dirt/sand.
- 2. Spray Bona Tile & Laminate Cleaner on +/- 3m² or spray directly on the cleaning pad.
- 3. Clean the surface with a mop and a cotton cleaning cloth and leave to dry. Clean the floor per 3m², then start the next part. Change cloths when it gets dirty.
- 4. Leave the floor to dry for at least 1h before walking on it. Attention: Reduce draft and dust to a minimum while the floor isn't dry.









4. ANNUAL CLEANING

Once or twice a year (depends on the usage of the floor) clean with Tile & Laminate Polish. You can find instruction under item 2 'First treatment after installation'.

5. STAINS

Stains from coffee, milk, wine, liqueurs, fruit juice, etc. can be removed with a damp cloth, possibly with some Bona Tile & Laminate Cleaner. Stains from asphalt, shoe polish, paint, ink, nail varnish etc. can be removed with a damp cloth with a few drops of pure acetone.

GREASE STAINS

If the grease stain does not disappear with a slightly damp cloth, Bona Fernox can be used. It is always advisable to test the product in a less visible place before treating the entire surface with it. Dilute 500-1000 ml Bona Fernox Parquet floor Degreaser with 10 litres of water. Mop the floor, let it soak briefly and wipe with a brush. Then mop using clean water.

PAINT STAINS / WAX / CHEWING GUM

If you cannot dislodge the dirt, after you have allowed it to dry, using your finger nail or a plastic scraper, a synthetic thinner may be the solution. Never use excessive amounts of the product.

6. SCRATCHES

Treat the surface with Bona Tile & Laminate Polish, as the polish will fill the scratches. Test this first in a less obvious place. Always treat the entire board. If necessary, you can apply tape around it. Polish is colourless: if the scratch has penetrated down to the decorative layer, it will only be possible to fill this scratch for protection purposes; the difference in colour will remain.



