

To Whom so ever it is concerned

The following is the recommended Load Bearing criteria for Everest Floor Boards :

Dry areas

Sheet thickness	Span	Allowable UDL (Kg/sq.m)		Allowable point load
		2 to 3 supports	Multiple supports	
mm	mm			kg
18	300	350	550	275
18	400	280	420	235
18	600	150	175	175
20	300	410	700	330
20	400	350	510	310
20	600	200	225	150

The following is the recommended Load Bearing criteria for Everest Heavy Duty Boards :

Wet areas

Sheet thickness	Span	Allowable UDL (Kg/sq.m)		Allowable point load
		2 to 3 supports	Multiple supports	
mm	mm			kg
15	300	550	800	400
15	400	450	710	300
15	600	210	300	200

The above values considers a Factor of Safety of 2.5



V.S.DEVARAJAN
DGM(R&D)
4/12/08

Everest Industries Limited

Lakhmapur Works : GAT. No. 152, Lakhmapur, Taluka Dindori, Nashik-422202 (Maharashtra)
Tel. : +91-2557-250375/462. Fax : +91-2557-250376

Head Office : Genesis A-32 Mohan Co-operative Industrial Estate Mathura Road New Delhi 110044 INDIA
Tel. : +91-11-41731951 Fax : +91-11-46566370 E-mail : info@everestind.com www.everestind.com