

CLEANING AND MAINTENANCE INSTRUCTIONS CLICWALL

Material specifications:

MDF panel, finished with a decorative metal melamine surface.

Applications:

Decorative wall panels for interior use as a non-bearing facing wall or partition.

Maintenance instructions:

Keep the area and walls dry with a relative humidity of 50 - 60% and maintain a room temperature between 15 and 20°C. ClicWall panels are not suitable for installation in damp and/or humid areas, in extremely dry areas or in areas with extremely high temperatures.

Thanks to a strong and hygienic melamine surface, Unilin ClicWall panels do not require any special maintenance or special maintenance products.

The product range contains various surface textures, which can be maintained just as easily as non-textured ones.

The recommended cleaning methods are as follows:

Light / recent soiling

Clean with a paper towel, a soft, clean cloth (dry or damp) or a sponge.

If you are using a damp cloth, the surface must be dried with an absorbent paper towel or microfiber cloth after wiping.

Normal soiling - long contact time

Clean with warm water, using a clean microfiber cloth, a soft sponge or a soft brush. Do not use too much water when cleaning! Choose a regular/standard household cleaning product or a soap without abrasive ingredients. The cleaning product must be distributed directly onto the soiled spot while cleaning. Next, wipe with fresh water and remove all traces of the cleaning agent to prevent stripes. Dry the surfaces with a clean absorbent cloth or a paper towel.

Never, in any case, use the following cleaning products:

- Abrasive and aggressive cleaning agents (scouring sponge, steel wool)
- Polish, laundry detergent, furniture cleaner, bleach
- Detergents with strong acids and salts
- Steam cleaning equipment